

# EV90P



## Indoor Unit



## G5 Performance

Airflow CFM	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
42	0.60	86	83/71
56	0.50	85	82/70
73	0.40	84	80/68
87	0.30	83	79/67
99	0.20	82	78/66
108	0.10	82	78/65

\* (See HVI certification report on page 72 for complete certified rating).

## Specifications

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 40-110 CFM				
Unit may be mounted in any orientation				
Number Motors: Two motorized impeller blowers				
V	HZ	Phase	Input Watts	FLA
120	60	Single	44 @ 90 CFM	0.35
Control: On board 24 VAC transformer/relay package with switched dry contacts				
Filters: MERV 8, spun polyester media. 21-3/4" x 10-1/2" x 1"				
Weight: 51 lbs (unit), 65 lbs (in carton)				
Shipping Dimensions: 32" L x 21-3/4" W x 28-3/4" H (in carton)				
Controls: PTL – Percentage Timer Control FM – Percentage Timer Control with Furnace Interlock PBL – Push Button Point-of-Use Controls				
Accessories: Wall Caps Back Draft Dampers				

## Dimensions

